

Low Cost DirectLine pH DL2000 Electrode Mountings For Use With DL421 Modules

Model Selection Guide

- Combines measuring and reference electrodes, together with integral fast responding automatic temperature compensator
- Temperature range 0 - 65° C (32 - 149° F)
- Pressure Spec 0 - 70 psig
- Suitable for in-line and immersion applications
- See Product Spec 70-82-03-59 for detail specifications



Instructions

- Select the desired key number. The arrow to the right marks the selection available.
 - Make the desired selections from Table I using the column below the proper arrow. A dot (•) denotes availability. No (•) dot denotes not available.
- Key Number**
- | | | | | |
|------------|---|-------|---|-------|
| Key Number | - | I | - | II |
| _ _ _ | | _ _ _ | | _ _ _ |

Key Number - Mounting/Electrode Only ¹ (Specify DL421 separately)	Selection	Availability
pH Electrode/Mountings	Electrode/Mountings for Glass pH version of DL421	DL2 ↓

TABLE I - Mounting Type, Construction, Cable Length

Mounting Type	Construction	Cable Length	Selection	Availability
In-Line or Immersion	Remote Mounting ²	20 feet	SX1	•

TABLE II - Factory Use

	Future Use	00 _ _	•
	Future Use	_ _ 00	•

- Note:** 1. DL421 electronics module must be specified separately
- Note:** 2. pH electrodes are supplied with a integral 6,1m (20 ft.) sensor cable which must be wired to the DL421 remote connector (ordered with DL421 Sensor Module).