

## Safety Data Sheet

### 1.0 Product Identifier

1.1 Material Name (PIN) – Corriculite™ 235 (CR235)

REACH Registration number – not applicable

1.2 Relevant uses – Filler Material for Spiral Wound Gaskets

1.3 – Details of the supplier –

Flexitallic Ltd, Scandinavia Mill, Hunsworth Lane, Cleckheaton,  
West Yorkshire, BD19 4LN, UK

Phone number – +44 (0)1274 851273

Emergency e-mail – [enquiries@flexitallic.eu](mailto:enquiries@flexitallic.eu)

1.4 Emergency telephone number - 01274 851273

### 2.0 Hazard identification

2.1 Classification of items within the mixture.

Regulation (EC) No 1272/2008 (CLP)	Hazard Statement
Vermiculite	Non-hazardous within the mixture
Elastomeric Binders	Non-hazardous within the mixture
Curing Agents	Non-hazardous within the mixture
Steatite	Non-hazardous within the mixture
Pigment	Non-hazardous within the mixture

2.2 Label Elements - not applicable to these products.

2.3 Other hazard information: – although substances used in the manufacture of this sealing, prior to production, present hazards from ingestion etc. – when contained within the sheet materials they do not present a hazard in any form nor can they be released.

### 3.0 – Information on ingredients.

3.1 – Ingredients within the mix used to produce this sheet are listed in section 2.1 of this document.

3.2 Mixtures – not applicable to this material.

#### **4.0 First aid measures**

##### **4.1 Description of first aid measures**

General information: – the materials used to produce this product do not present any risk to the user in its encapsulated form. However when cutting operations are being carried out there is a low probability of dust or fume release.

In accordance with best practise the work should be carried out in a well-ventilated area or an engineering solution provided (Local Exhaust Ventilation – LEV). However if this is not possible then respiratory protection can be used.

Skin contact – always wash well after handling these products.

Eye contact – flush the eye(s) with clean water.

Ingestion – highly improbable.

##### **4.2 Symptoms – some mild skin irritation can occur.**

##### **4.3 Indications of immediate medical attention being required – none.**

#### **5.0 Fire Fighting measures –**

General: – the material will burn with difficulty in a sustained fire situation but will tend to self-extinguish when the source of ignition is removed.

##### **5.1 Extinguishing media: – Water or foam.**

Dry chemical powder and carbon dioxide may also be used. In view of the comments in 'general' the source of the fire should be dealt with in accordance with requirements and the material will then self-extinguish.

##### **5.2 Special hazards arising from the material - very low level of irritant fumes and toxic gases.**

##### **5.3 Advise to fire fighters:-none.**

#### **6.0 Accidental release measures**

##### **6.1 Personal precautions etc. - none.**

##### **6.2 Environmental precautions – none.**

## **7.0 Handling and storage**

7.1 Gloves should be worn when handling these materials.

7.2 Conditions for safe storage - none.

7.3 Specific end uses - refer to appropriate technical data sheet.

## **8.0 Exposure controls/personal protection**

Not applicable to these products.

## **9.0 Physical Properties.**

- Physical state – solid.
- Colour and appearance – Spiral wound gasket filler material, green in colour.
- Odour threshold – NA
- Vapour pressure – NA
- Vapour density – NA
- Evaporation rate – NA
- Boiling point – NA
- Freezing point – NA
- pH – NA
- Specific gravity – NA
- Coeff. Water/Oil Dist. – NA

## **10.0 Stability and reactivity**

10.1 Reactivity – NA

10.2 Chemical stability – NA

10.3 Possibility of hazardous reactions – NA

10.4 Conditions to avoid – NA

10.5 Incompatible materials –NA

10.6 Hazardous decomposition products - NA

## **11.0 Toxicological Information.**

Not applicable to these products

## **12.0 Ecological Information**

- 12.1 Toxicity – NA
- 12.2 Persistence and degradability – NA
- 12.3 Bio accumulative potential – NA
- 12.4 Mobility in soil – NA
- 12.5 Results of PBT and vPvB assessment - NA
- 12.6 Other adverse effects – NA

## **13.0 Disposal considerations**

- 13.1 All waste should be disposed of in accordance with the requirements of local regulations. Consideration should also be given to the potential for re-cycling or, if possible, by environmentally friendly routes. These could include re-cycling or the use of waste in Refuse Derived Fuel plants.

## **14.0 Transport considerations**

No special requirements

## **15.0 Regulatory information**

- 15.1 Safety, Health and Environmental regulations – NA
- 15.2 Chemical safety assessment – NA

## **16.0 Other information**

**Date This Document Was Created – May 2017**

**Date of issue – May 2017**

**Brief description of changes since the last version – Not applicable**

**List of abbreviations – vPvB – very Persistent very Bio accumulative**

**Issuing authority - Flexitallic Applications Engineering Department**

**Total Pages - 4**