

DECLARATION OF CONFORMITY

We: **Yokogawa Process Analyzers Europe B.V.**
Euoweg 2
3825 HD Amersfoort
The Netherlands

herewith declare under our sole responsibility that the product, model: **PR10**
further specified with model suffix- and option codes: **As listed in Annex-1 in this document**
is manufactured in accordance with the following standards:


EN-ISO 9001: 2008 Quality management systems - Requirements

Subject product is:

- In compliance with the essential requirements of the specific product legislation:
 - **Pressure Equipment** **Directive 97/23/EC (PED)**
As amended by Regulation (EC) no. 1882/2003, by applying:
Article 3.3: Sound Engineering Practice
- Produced according to appropriate quality control procedures.

If applicable, the product is checked against the latest official released revision of the standards mentioned above; differences do not affect the product identified on this declaration.

Amersfoort - July 01, 2014


H. Leijten
General Manager
Yokogawa Process Analyzers Europe B.V.

Annex-1

Model	Suffix	Options	Description
PR10			Retractable fitting general purpose
Material fitting	-S		Stainless steel
	-T		Titanium (tube and sensor holder only)
Material O-rings	-V		Viton
Tube length	-L5		Tube length 0.5 meter
Connection	-D32		DN32 / 1¼"
	-D50		DN50 / 2"
Measuring sensor	-PH12		For 12mm pH sensors Y-cap
	-PH13		For 12mm pH sensors PG13.5 cap
	-SC4A		For SC4A
	-ISC4		For ISC40
	-NNNN		No parameter specification
Adapter screw-in		/SA125	ISO 228/1 G1¼ to 1¼" M-NPT
		/SA200	ISO 228/1 G2 to 2" M-NPT
Flange adapter		/FA125	Flange adapter drain 1¼" 150 Lbs
		/FN125	Flange adapter no drain 1¼" 150 Lbs
		/FA200	Flange adapter drain 2" 150 Lbs
		/FN200	Flange adapter no drain 2" 150 Lbs
		/FAD32	Flange adapter drain DN32 PN10
		/FND32	Flange adapter no drain DN32 PN10
		/FAD50	Flange adapter drain DN50 PN10
		/FND50	Flange adapter no drain DN50 PN10
Adapter weld-in		/WA125	Straight weld-in adapter ISO 228/1 G1¼
		/WA200	Straight weld-in adapter ISO 228/1 G2
Ball-valves		/BF125	Ball-valve flanged 1¼" 150 Lbs
		/BF200	Ball-valve flanged 2" 150 Lbs
		/BFD32	Ball-valve flanged DN32 PN10
		/BFD50	Ball-valve flanged DN50 PN10
		/BS125	Ball-valve screw-in 1¼" F-NPT
		/BS200	Ball-valve screw-in 2" F-NPT
Certificates		/M	Material certificate 3.1 according to EN-10-024 (DIN50-049) (on wetted parts).